SENTINEL®
Connector Systems Inc.

RJ45 Power over Ethernet (PoE) Plug Finder

Can be used for ALL 15W PoE (IEEE 802.3af), 30W PoE+ (IEEE 802.3at), 60W PoE++ (IEEE 802.3bt Type 3) and 100W PoE++ (IEEE 802.3bt Type 4) Applications

Key Dimensions based on Insulated Conductor OD and Jacket OD

	Unshielded Plugs					Shielded Plugs			
Part Number	Picture	Category	Insulated Conductor OD	Jacket OD	Part Number	Picture	Category	Insulated Conductor OD	Jacket OD
106-080800-34		5e	.037" - .042"	Up to .240"	-	-	-	-	-
106-08080058-34		5e	Up to .048"	.240" - .260"	106S08080058C34		5e	Up to .048"	Up to .265"
111-0808LB16-34		5e	.037" - .042"	.240" - .260"	111S08080016-34		5e	.037" - .042"	.240" - .260"
-	-	-	-	-	111S08080028C34		5e	.037" - .042"	.240" - .260"
111-08080028L34		5e	.037" - .042"	.240" - .260"	111S08080028L34		5e	.037" - .042"	.240" - .260"
111-080800-34		6	.037" - .042"	.240" - .260"	-	-	-	-	-
111-08080054L34		6	.037" - .042"	.240" - .260"	111S08080054L34		6	.037" - .042"	.240" - .260"
-	-	-	-	-	111S08080054C34		6	.037" - .042"	Up to .275"
-	-	-	-	-	111S08080054H34		6	.037" - .042"	Up to .310"
111-08080056-34		5e	.039" - .043"	.240" - .260"	111S08080056-34		5e	.039" - .043"	.240" - .260"
111-08080090L34		6A/6	.044" - .048"	.240" - .260"	111S08080090L34		6A/6	.044" - .048"	.240" - .260"
-	-	-	-	-	111S08080090C34		6A/6	.044" - .048"	Up to .275"
-	-	-	-	-	111S08080090H34		6A/6	.044" - .048"	Up to .310"
111-08080091L34		6A/6	.048" - .0525"	.240" - .260"	111S08080091L34		6A/6	.048" - .0525"	.240" - .260"
-	-	-	-	-	111S08080091C34		6A/6	.048" - .0525"	Up to .275"
-	-	-	-	-	111S08080091H34		6A/6	.048" - .0525"	Up to .310"